



# S60-S Portable Payment Terminal

**PAX's S60-S** is a unique device featuring a compact, ruggedized and yet lightweight POS terminal into a docking station with communications and high-speed sprocket printer (or optional thermal printer)

Equipped with a built-in secure PIN pad, PCI PTS 4.x certified, the portable handset provides a secure and convenient payment experience for merchants and cardholders. With 4 ATM style keys, the S60-S streamlines payments and enhances the customer experience, offering ease of use for both merchant and consumers.

The S60-S is designed for payments at the point of service, such as restaurant and hotel environments, making it a powerful solution for a variety of business applications.

# S60-S Portable Payment Terminal

## FEATURES & BENEFITS



- PCI PTS 4.x certified
- Sprocket printer
- Large Memory Capacity
- Optional contactless card reader
- Ruggedized and portable design
- Multi-Application Support
- Multiple connectivity options-Ethernet & Dial
- Ideal with hospitality merchants

## SPECIFICATIONS

### Handset

#### Processor

32-bit, ARM11

#### Memory

192MB (128MB Flash, 64MB DDR)

#### Display

128 x 64 pixel LCD  
White backlit

#### Keypad

10 numeric keys  
4 ATM keys, 8 function keys,  
1 power ON/OFF key

#### Magnetic Card Reader

Track 1/2/3, bi-directional

#### Smart Card Reader

EMV L1 & L2 certified

#### Contactless Card Reader (optional)

13.56MHz, ISO14443 Type A/B  
Mifare, Felica, NFC  
4 RF Indicators

#### Card Slots

3 SAMs

#### Communication

Infrared communication

#### Voltage

Li-ion battery, 750mAh

#### Peripheral Port

1 x mini USB

#### Security

DUKPT, Master/Session, DES, 3DES  
ANSI/ISO9564 format 0, 1, 3  
PIN ciphered key algorithm  
ANSI X9.9/X9.19 MAC algorithm

#### Environmental

0°C to 50°C (32°F to 122°F)  
operating temperature  
10% to 93% relative humidity,  
non-condensing  
-20°C to 70°C (-4°F to 158°F)  
storage temperature

#### Physical

Length: 165mm  
Width: 84mm  
Height: 35mm

#### Weight

302g

#### Base

#### Processor

32bit ARM

#### Memory

12MB

#### Printer

Sprocket printer, Speed: 4 lines/second  
Standard paper width: 76.2±0.5mm

#### Peripheral Ports

2 x RS232, 1 x PINpad, 1 x Line  
1 x Ethernet (optional)

#### Communication

Modem: Sync. (HDLC up to 9600bps)  
Async. (V.92, up to 56Kbps)  
Ethernet (optional)

#### Environmental

0°C to 50°C (32°F to 122°F)  
operating temperature  
10% to 93% relative humidity,  
non-condensing  
-20°C to 70°C (-4°F to 158°F)  
storage temperature

#### Voltage

Input: 100~240VAC, 50Hz/60Hz, 1.5A  
Output: 24VDC, 1.8A

#### Physical (with paper holder)

Length: 298mm  
Width: 149mm  
Height: 97mm

#### Weight

898g

#### Certifications

PCI PTS 4.x  
EMV L1 & L2

[www.pax.com.cn](http://www.pax.com.cn)

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.  
PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries.  
All other trademarks or brand names are the properties of their respective holders. Copyright 2016, PAX Technology Limited, All Rights Reserved.





# S60-T Portable Payment Terminal

**PAX's S60-T** is a unique device featuring a compact, ruggedized and yet lightweight POS terminal into a docking station with communications and high-speed thermal printer (or optional sprocket printer)

Equipped with a built-in secure PIN pad, PCI PTS 4.x certified, the portable handset provides a secure and convenient payment experience for merchants and cardholders. With 4 ATM style keys, the S60-T streamlines payments and enhances the customer experience, offering ease of use for both merchant and consumers.

The S60-T is designed for payments at the point of service, such as restaurant and hotel environments, making it a powerful solution for a variety of business applications.

# S60-T Portable Payment Terminal

## FEATURES & BENEFITS



- PCI PTS 4.x certified
- Fast thermal printer
- Large Memory Capacity
- Innovative and portable design
- Optional contactless card reader
- WiFi, Ethernet, Dial
- Ideal with hospitality merchants

## SPECIFICATIONS

### Handset

#### Processor

32-bit ARM11

#### Memory

192MB (128MB Flash, 64MB DDR)

#### Display

128 x 64 pixel LCD  
White backlit

#### Keypad

10 numeric keys  
4 ATM keys, 8 function keys,  
1 power ON/OFF key

#### Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

#### Smart Card Reader

EMV L1 & L2 certified

#### Contactless Card Reader (optional)

13.56MHz, ISO14443 Type A/B,  
Mifare, Felica, NFC  
4 RF Indicators

#### Card Slots

3 SAMs

#### Communication

Infrared communication

#### Peripheral Port

1 x mini USB

#### Voltage

Li-ion battery, 750mAh

#### Security

DUKPT, Master/Session, DES, 3DES  
ANSI/ISO9564 format 0, 1, 3  
PIN ciphered key algorithm  
ANSI X9.9/X9.19 MAC algorithm

#### Environmental

0°C to 50°C (32°F to 122°F)  
operating temperature  
10% to 93% relative humidity,  
non-condensing  
-20°C to 70°C (-4°F to 158°F)  
storage temperature

#### Physical

Length: 165mm  
Width: 84mm  
Height: 35mm

#### Weight

302g

#### Base

#### Processor

32bit ARM 9

#### Memory

12MB

#### Printer

Thermal graphic printer,  
speed : 30 lines per second  
Paper roll width / diameter: 58mm / 50mm

#### Peripheral Ports

2 x RS232, 1 x PINpad, 1 x Line,  
1 x Ethernet (optional)

#### Communication

Modem: Sync. (HDLC up to 9600bps)  
Async. (V.92, up to 56Kbps)  
Ethernet (optional)  
WiFi (optional)

#### Environmental

0°C to 50°C (32°F to 122°F)  
operating temperature  
10% to 93% relative humidity,  
non-condensing  
-20°C to 70°C (-4°F to 158°F)  
storage temperature

#### Voltage

Input: 100~240VAC, 50Hz/60Hz, 1.5A  
Output: 8.2VDC, 2.5A

#### Physical (with paper holder)

Length: 230mm  
Width: 104mm  
Height: 86mm

#### Weight

680g

#### Certifications

PCI PTS 4.x  
EMV L1 & L2

[www.pax.com.cn](http://www.pax.com.cn)

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. Copyright 2016, PAX Technology Limited, All Rights Reserved.