

Q60

CLASSIC

Mobile



Food & Beverage



Fashion & Retail



Supermarkets



CLASSIC



Powered by
Prolin



PCI 6
SRED



2.4"
Display


















0.3MP
Rear



Advanced
Connectivity

SPECIFICATIONS

	Operating System	Prolin
	Processor	Cortex A7
	Memory	128MB Flash, 128MB DDR (Optional: 256MB Flash, 256MB DDR)
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Cameras	Optional 0.3MP Rear-Facing
	Display	2.4" 240 x 320 Color Screen
	Comms Configurations	GPRS / WCDMA / CAT-1 Wi-Fi® (optional) Bluetooth® 4.2 (optional)
	Battery	2450mAh 3.6V
	Adapter	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
	Printer	Thermal Printer Speed : 40mm/s (20lp/s) Width: 58mm Diameter: 40mm
	SIM / SAM	1 Micro SAM + 1 Micro SIM 2 Micro SIM
	Keys / Buttons	10 Numeric Keys 8 Function Keys 1 Power Key
	Audio	1 Buzzer
	Ports	1 Type-C (OTG)
	Physical	150 x 76 x 52mm
	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-Condensing
	Certifications	PCIPTS 6.x EMV L1 & L2 EMV contactless L1 qUICS L2 Mastercard contactless Visa PayWave American Expresspay Discover D-PAS ABECS Anatel CE RoHS TQM

