

D135

CONTACTLESS mPOS



Micro & Small Merchants



Fashion & Retail



Food & Beverage



CLASSIC



Powered by
Monitor



PCI 5
SRED



Flexible
Platform


















Pin on
Mobile



Pocket
Sized

SPECIFICATIONS

	Operating System	Monitor
	Processor	Cortex M3
	Memory	Built-in 1MB FLASH + 128KB SRAM External 4MB SPI Nor Flash for Fonts, Config Files
	Card Readers	Chip & PIN Contactless Magnetic Stripe (optional)
	Contactless	ISO14443 Type A/B, Mifare®
	Comms Configurations	Bluetooth®4.2 , Supports : Bluetooth® Low Energy 1 Type-C Optional Pogo PIN
	Battery	250mAh Optional 400mAh
	Keys / Buttons	1 Button: Power On / Power Off / Sleep / Pair to Bluetooth® COTS
	Indicators	4 RF Indicators, 1 Power Indicators (green & red)
	Cable	1 USB Cable
	Audio	1 Buzzer
	Ports	1 Type-C OTG POGO PIN (optional)
	Physical	13 x 67 x 67 mm, 63.6g (with MSR)
	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10%-93% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 5.x SRED EMV L1 & L2 EMV CL L1 Mastercard contactless L2 Visa payWave L2 DPAS L2 QUICS L2 AMEX L2 InteacFlash L2 TQM UL FCC IC RoHs

