

S300

TRADITIONAL Smart PINpad



Supermarkets



Fashion & Retail



Food & Beverage



CLASSIC



Powered by
Prolin / PaxMe



PCI 4
SRED



3.5"
Display




Pole Stand
Option

S300

Smart PINpad

SPECIFICATIONS

	Operating System	Prolin/PaxMe
	Processor	32-bit ARM 11
	Memory	128MB Flash + 64MB DDR
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Display	3.5" TFT QVGA 240 x 320 Pixels Touch Screen
	Comms Configurations	RS232 USB 2.0 Fast Ethernet
	SIM / SAM	3 Micro SAMs
	Keys / Buttons	15 Keys: Func 0 ~ 9 Alpha Enter Clear Cancel Back-Lighting
	Audio	1 Speaker
	Ports	Single Multi-Port Connector: 2 RS232 1 USB2.0 1 Fast Ethernet 1 Power
	Physical	167 x 81 x 50mm, 290g
	Power Supply	External Power Supply 5V DC, 0.5A
	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-Condensing
	Accessories	PS200 Pole Stand Multi-Function Cable
	Certifications	PCI PTS 4.x, SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs

